



Multimat Cube/Cube press  
Porcelain Furnaces

# Cube your firing performance

Brochure for the dental laboratory

# Cube your firing performance

The ultimate combination of performance, usability and reliability



## High Performance

- + High temperature stability and multi-stage heating and cooling programs ensure great results when pressing and firing of common dental ceramic systems, including lithium silicate/disilicate ceramics.



## Ultimate Reliability

- + Extensive 72h stress testing, two year warranty and technical support ensure ongoing reliability.
- + Intelligent pre-heating program.
- + Secure placement of your restoration, due to the movable chamber, which avoids vibration of the firing tray.
- + “Made in Germany” quality, approved according to international and ETL standards.



\* Multimat Cube press is a pressing and firing unit

\*\* Multimat Cube is the identical unit without the pressing option



## Intuitive Usability

- + User friendly large touch display with intuitive user interface gives clear access to programs and makes it easy for everybody to use. LED status display saves time, keeping users up to date from a distance.
- + Firing/pressing programs of Dentsply Sirona porcelain systems are pre-installed.
- + Two USB ports for data backup, update function via USB-Stick.



## Modern Design - Fits seamlessly into the dental environment

- + Premium materials and minimalistic design ensures it stands out and looks great.
- + Glas-Touch-Display with 3 mm reinforced glass.

# Technical specifications

## Multimat® Cube

Height: closed	approx. 475 mm	Voltage:	100 – 115 V	REF 54 6028 0002
opened	approx. 645 mm		220 – 230 V	REF 54 6028 0001
Width:	approx. 310 mm	Frequency:	50 – 60 Hz	
Depth:	approx. 470 mm	Power consumption:	1,580 W including vacuum pump (at 220 – 230 V) 1,580 W including vacuum pump (at 100 – 115 V)	
Weight:	approx. 26.5 kg			

## Multimat® Cube press

Height: closed	approx. 575 mm	Voltage:	100 – 115 V	REF 54 6028 0012
opened	approx. 745 mm		220 – 230 V	REF 54 6028 0011
Width:	approx. 310 mm	Frequency:	50 – 60 Hz	
Depth:	approx. 470 mm	Power consumption:	1,580 W including vacuum pump (at 220 – 230 V) 1,580 W including vacuum pump (at 100 – 115 V)	
Weight:	approx. 29 kg			

Specific technical characteristics	
Opening range, base to firing chamber	100 mm
Closing time, firing chamber	approx. 19 seconds.
Ambient temperature, operation	+5 °C to +40 °C, ideal: +20 °C
Ambient temperature, storage	0 °C to +40 °C
Humidity	80% relative humidity at temperatures up to 31 °C or linear decrease to 50% at +40 °C
Environment	Indoors only, on a non-flammable surface
Heating Element	Quartz muffle with an openly radiating filament
Maximum firing temperature	1200 °C
Heating rate	Up to 120 °C/min
Pressure in pressing mode	0 to 3 bar, monitored
Display	7" TFT LCD display with projective capacitive touch, 3 mm thermally hardened flat glass, 800 × 480 pixels

### Accessories:

REF D 03 532 803 Silver wire test

REF D 03 002 220 VD Vacuum pump, 230 V/50 Hz including filter

Technical specifications may change without notice



DeguDent GmbH  
 Rodenbacher Chaussee 4  
 63457 Hanau-Wolfgang  
 Germany  
 +49 6181 59-50  
 www.dentsplysirona.com

Dentsply Sirona  
 1301 Smile Way  
 York  
 PA 17404  
 USA

40101/REV 2021-02